



## S-4180-GX+

### MULTI SATELLITE DUAL SATELLITE 8-WAY

4 LNBF and one UHF/VHF inputs and 8 outputs. For use with DIRECTV elliptical dish dual or triple satellite systems. Can be used with S-5040Y-CE to extend to 8 receivers.

<b>Model Number</b>	<b>S-4180-GX+</b>
<b>Frequency Range</b>	
Satellite	950 – 2200 MHz
Off-air	54 – 806 MHz
<b>Satellite</b>	
Insertion Loss / Gain	-2 to +5 dB
Same Sat. Cross-Pol. Isolation	30 dB
Diff. Sat. Cross-Pol Isolation	35 dB
<b>Selection Control Voltage</b>	
18V (101 LHCP)	16.75 – 21VDC
13V (101 RHCP)	11.75 – 14VDC
18V 22kHz (119 LHCP + 110)	16.75 – 21VDC, w 22kHz
13V 22kHz (119 RHCP)	11.75 – 14VDC, w 22kHz
<b>Off-air</b>	
Insertion Loss	5 dB
<b>Others</b>	
Output Ports	8
Indoor or Outdoor	Indoor
22kHz Tone Output at 18V/22kHz and 13V/22kHz	Yes
DC Adapter Requirement	Required
Dimensions	8.5"x3.75"x1"
<b>DC Adapter</b>	
AC Input	115 VAC
DC Output Voltage	24 VDC
Max DC Current	1000 mA